

Management System ISO 9001:2015 www.tuv.com



VISION 6

The armored vending machine

Next-generation vending Automated kiosks for any kind of product Magex patented system spiral-free

FEATURES



10" Monitor



Payments system setup



6 lanes modular shelves



Break-proof Glass



Internal LED lighting



OPTIONS

- Sanification system
- Loyalty card & customer App integration
- Temperature control

USER EXPERIENCE

Quad-Core CPU 10" touchscreen panel, 1920x1080 full HD for an e-commerce-like user experience.

The screen provides a menu where the consumer can browse product descriptions, promotional images and videos.

REAL-TIME DATA SERVICE

Magex provides a vending machine real-time management service, thanks to our web-based interface accessible from virtually any kind of device.

You can check real-time selling statistics, stock status, actual stock for every currency denomination.

You will be able to monitor the internal temperature and visualize it in a chart.





MAGEX PATENTED DISPENSING SYSTEM

AUTOMATED RETAIL


Magex vending machines boast unprecedented flexibility in managing very different items.

Our Conveyer patented dispensing system fits any kind of product, also combining adjacent lanes to move larger products.

End-user can easily customize lanes setup to manage effectively any size and shape item to sell.


Moreover, interlocking partitions keep items separate into the same lane.

Our advanced multi-function self-diagnostic tool performs a continuous system health check, starting from lanes operation status before each delivery up to a full system reboot if needed.



LIFT DELIVERY SYSTEM

Our internal lift system gently delivers any kind of items in the withdrawal area under the window.



VISION 6

A SOLID AUTOMATIC KIOSK

The armored chassis makes it especially suitable for outdoor employment.

The large deep window stocks a large number of products, endowing a charming display view.

DATA SHEET

Width	901 mm
Height (with cooling unit)	1982 mm (2282)
Depth	883 mm
Withdrawal area	472 x 180 mm
Number of floors standard/ max	8
Lanes per floor	6
Voltage supply	230V/50Hz 110V/60Hz

